


Specifications

Ingenuous, reliable, service-friendly and maximal productivity
That is the power of SDPi



Type SDP		20 S	25 S	32 S	42 S
Information					
Machine class (t)		15 - 25	22 - 35	32 - 50	45 - 70
Weight (kg)*		2100	2765	3100	4500
Cycclus open/close (s.)		1,9 - 1,2	2,2 - 2,4	2,5 - 2,8	2,6 - 2,8
Closing force at position 1 (t)		62	70	95	105
Closing force at position 2 (t)		100	107	152	195
Dimensions					
Dimension A (mm)		2100	2270	2458	2640
Dimension B (mm)		760	760	760	880
Dimension C (mm)		390	479	495	556
Dimension D (mm)		310	350	398	470
Dimension E (mm)		750	822	867	930
Dimension F (mm)		900	1040	1090	1290
Dimension G (mm)		200	200	200	250
Attachement					
Rotar Hole-pattern		140 - 150	140 - 150	140 - 150	150
Hydraulic					
Max. operating pressure cylinder (bar)		350	350	350	350
Oil volume cylinder (L/min)		150 - 250	150 - 250	250 - 300	250 - 300
Max operating pressure motor (bar)		170	170	170	170
Oil volume motor (L/min)		40 - 60	40 - 60	40 - 60	40 - 60

* Weight exclusive adapterplate with bracket
** Figures given for cycle times and cutting forces are indications only. External factors such as excavator setting, hydraulic infrastructure, quickcouplers and fittings may influence performance.
*** Technical specifications are subject to change without prior notice.

Strive Engineering Solutions OPC Pvt Ltd
Jhinga Road, Chational, Kurali, Mohali 140103
info@striveengineering.com +91-94640-36982

SDP-series



STENSOL